

CODE	ITEM	DESCRIPTION	COLOUR	SUPPLIER	LOCATION	
GT-05	Glass Type 5 Mirror glass	Décor-mirror	Mirror	Viridian	Dis WC	
LM-1	Laminate	Laminex (Formica) Laminate	Graphite (7837) (Velour finish)	Laminex	General joinery	Sample to be provided, prior to order.
Internal Joinery Carcass	Laminate	Laminex laminate	White	Laminex	Joinery carcasses generally	Melamine with white laminate for Joinery carcasses generally
P-01	Interior Wall Paint 1: General Wall color	Dulux Professional Enviro2 Interior low sheen	Limed White ½	Dulux www.dulux.com.au	Dis WC	1m x 1m sample to be approved
P-02	Interior Door Paint	Dulux 'Weathershield'	Monument, Low Sheen Acrylic, 3 coats	Dulux www.dulux.com.au	Dis WC	1m x 1m sample to be approved
PB-01	Plasterboard	13mm Gyprock, standard plasterboard	Paint Finish as specified	Gyprock www.gyprock.com.au	Dis WC	
WPB-01	Waterproof plasterboard	13mm Gyprock, Aquachek, plasterboard	Paint Finish as specified	Gyprock www.gyprock.com.au	Dis WC	
SS-01	Benchtops and splashback in Kitchen	Corian	Lava Rock (E), with Sikaflex Pro Concrete Grey silicon	Corian	Kitchenette	Sample to be approved prior to ordering
CPT-01	Carpet	Supertuft Escape Twist	Swat	Supertuft www.supertuft.com.au	General Carpet	Sample to be approved prior to ordering
CPT-02	Carpet	Supertuft Escape Twist	Swat	Supertuft www.supertuft.com.au	General Carpet	Sample to be approved prior to ordering
CPT-TRM-1	Carpet Trim	Anodized aluminum edge strip	Powdercoated to match carpet colour		Carpet to Tile Floor Finish Transition	Sample to be approved prior to ordering
CPT-TRM-2	Carpet Trim	Anodized aluminum edge strip	Powdercoated to match carpet colour		Carpet to timber Floor Finish Transitions	Sample to be approved prior to ordering
VN-01	Vinyl	"Accolade Safe Plus"	Black Opal'	Armstrong	Dis WC	Sample to be approved prior to ordering
PP-01	Patch and Polish				General Timber Floor finish	Sample to be approved prior to ordering

CODE	ITEM	DESCRIPTION	COLOUR	SUPPLIER	LOCATION	
CSH-01	Cushion Flooring	Tarflex Multiuse 6.2 Sports Flooring	-Wood Black 8840	Gerflor	West Nave	Sample to be approved prior to ordering
MATTWELL	Front Entry Matt Well	Birrus Duramat	Black	Birrus http://www.birrusmatting.com.au/	Entry	Contractor to allow for appropriate set down in slab to allow for a flush transition with adjacent floor finishes
TC-1	External Tactile Indicators	'Endura' Discrete Tactile Surfaces Indicators	Stainless Steel	TGSI www.tactileindicators.net	Entry.	To comply with relevant Australian standards
	Emergency Signage	Vinyl Lettering	Black	By Contractor	Fire Hose Reel Door, Refer to D&w schedule	Architect to approve text size, font & colour prior to order.

GENERAL NOTES:

NOTE 1: Early Fire Hazard Indices (Clause C1.10 & C1.10a)

All new fixed surface finishes to comply with the following Fire Hazard Indices:

Floor Materials/Coverings, Walls & Ceiling Linings

Floor materials and floor coverings, have a Critical Radiant Heat Flux (CRF) not less than 2.2kW/M² or 1.2kW/M² when building is protected by a sprinkler system. In a building not protected by a sprinkler system, have a maximum smoke development rate of 750%/minutes.

Wall and ceiling lining materials must be group number 1, 2 or 3 as required by BCA Specification C1.10a.

Other Materials

Spread of Flame Index ≤ 9

Smoke Developed Index ≤ 8 if the Spread of Flame Index is more than 5

Details of fire tests for each of these surfaces are to be provided for approval prior to their installation.